

## Příloha č.1 k VZ Inovace technologie odběrných míst TMV – komponenty Siemens

Množství	Objednací číslo	Popis výrobku
10	6ES7215-1AG40-0XB0	SIMATIC S7-1200, CPU 1215C, compact CPU, DC/DC/DC, 2 PROFINET ports, onboard I/O: 14 DI 24 V DC; 10 DO 24 V DC; 0.5A; 2 AI 0-10 V DC, 2 AO 0-20 mA DC. Power supply: DC 20.4-28.8V DC, Program/data memory 125 KB
10	6ES7221-1BH32-0XB0	SIMATIC S7-1200, Digital input SM 1221, 16 DI, 24 V DC, Sink/Source
10	6ES7231-5ND32-0XB0	SIMATIC S7-1200, Analog input, SM 1231, 4 Ai, +/-10 V, +/-5 V, +/-2.5 V, +/-1.25 or 0-20 mA/4-20 mA, 15 bit+sign bit
10	6EP1333-3BA10	SITOP PSU200M 5 A Stabilized power supply input: 120/230-500 V AC output: 24 V DC/5 A
10	6EP4136-3AB00-2AY0	SITOP UPS1600 20 A Ethernet/ PROFINET Uninterrupted power supply with Ethernet / PROFINET interface / OPC UA Server / Web server input: 24 V DC output: 24 V DC/20 A
100	LZS:RT17040	Label 15 mm for RT and RY relay